

**Upholstery Leather** Technical Data**Leather Specifications**

Style:	Arizona (AR)
Description:	Full grain, aniline dyed lightly finished leather
Thickness:	0.9–1.0 mm
Weight:	2.25–2.50 oz. per sq. ft.
Average Hide Size:	55–60 sq. ft.
Finish:	Breathable protective finish

**Performance Characteristics****Tests**

Light Fastness (AATCC Method 16, Option E, 72 Hours)	Class 4
Crocking (ASTM D-5053):	Dry: Class 4      Wet: Class 3
Abrasion (ASTM D-3884):	300+ cycles (CS-10 wheels)
Flex (ASTM D-2097):	70,000 cycles
Tearing Strength, Double Hole (ASTM D-4705):	25 lbs.
Breaking Force (ASTM D-2208):	150 lbs.
Elongation (ASTM D-2211):	30-50% at 50 lbs.

**Flammability***Passes the following flammability tests*

California Technical Bulletin 117	Complies
Boston Fire Dept. BFD IX-1	Complies (with flame treatment)
Cigarette Ignition Resistance (NFPA-260)	Class I
Surface Burning Characteristics of Bldg. Materials (ASTM E84)	Class II (Class I with flame treatment)
IMO Resolution A.652 (16)	Complies
IMO Resolution A.653 (16)	Complies

\*Successfully used in CAL 133 applications with Firegard F187 fire backer material or equivalent.

**Recommended Cleaning Instructions**

Dust regularly. Minor spots can be washed off using lukewarm water and mild soap.

Do not soak. Never clean with abrasive solvents, alcohol, or wax-based products.

Approved maintenance products are available from Spinneybeck.