

Upholstery Leather Technical Data**Leather Specifications**

Style:	Copenhagen (CO)
Description:	Full grain, aniline dyed, naked leather
Thickness:	1.1–1.2 mm
Weight:	2.75–3.00 oz. per sq. ft.
Average Hide Size:	45–50 sq. ft.
Finish:	Naked

Performance Characteristics**Tests**

Light Fastness (AATCC Method 16, Option E, 72 Hours)	Class 2-3
Crocking (ASTM D-5053):	Dry: Class 2-3
Abrasion (ASTM D-3884):	N/A
Flex (ASTM D-2097):	N/A
Tearing Strength, Double Hole (ASTM D-4705):	25 lbs.
Breaking Force (ASTM D-2208):	200 lbs.
Elongation (ASTM D-2211):	30-60% at 50 lbs.

Flammability*Passes the following flammability tests*

California Technical Bulletin 117	Complies
Surface Burning Characteristics of Bldg. Materials (ASTM E84)	Class II

*Successfully used in CAL 133 applications with Firegard F187 fire backer material or equivalent.

Recommended Cleaning Instructions

Dust regularly. Minor spots can be washed off using lukewarm water and mild soap.

Do not soak. Never clean with abrasive solvents, alcohol, or wax-based products.

Approved maintenance products are available from Spinneybeck.