

Capri (CP)

Upholstery Leather Technical Data**Leather Specifications**

Style:	Capri (CP)
Description:	Full grain, aniline dyed, chrome free leather
Thickness:	1.2–1.4 mm
Weight:	3.0–3.5 oz. per sq. ft.
Average Hide Size:	55–60 sq. ft.
Finish:	Breathable, light, protective finish

Performance Characteristics**Tests**

Light Fastness (AATCC Method 16, Option E, 72 Hours)	Class 4
Crocking (ASTM D-5053):	Dry: Class 4 Wet: Class 3
Abrasion (ASTM D-3884):	300+ cycles (CS-10 wheels)
Flex (ASTM D-2097):	70,000 cycles
Tearing Strength, Double Hole (ASTM D-4705):	25 lbs.
Breaking Force (ASTM D-2208):	200 lbs.
Elongation (ASTM D-2211):	50-70% at 50 lbs.

Flammability

Passes the following flammability tests

California Technical Bulletin 117	Complies
Boston Fire Dept. BFD IX-1	Complies
Surface Burning Characteristics of Bldg. Materials (ASTM E84)	Class II
IMO Resolution A.652 (16)	Complies
IMO Resolution A.653 (16)	Complies

*Successfully used in CAL 133 applications with Firegard F187 fire backer material or equivalent.

Recommended Cleaning Instructions

Dust regularly. Minor spots can be washed off using lukewarm water and mild soap.

Do not soak. Never clean with abrasive solvents, alcohol, or wax-based products.

Approved maintenance products are available from Spinneybeck.