

## Ducale Velour (DV)

### Upholstery Leather Technical Data

#### Leather Specifications

Style:	Ducale Velour (DV)
Description:	Full grain, aniline dyed leather
Thickness:	1.2–1.3 mm
Weight:	3.0–3.25 oz. per sq. ft.
Average Hide Size:	50–55 sq. ft.
Finish:	Impregnated soil-resistant treatment

#### Performance Characteristics

#### Tests

Light Fastness (AATCC Method 16, Option E, 72 Hours)	Class 2-3
Crocking (ASTM D-5053):	Dry: Class 2–3
Abrasion (ASTM D-3884):	N/A
Flex (ASTM D-2097):	N/A
Tearing Strength, Double Hole (ASTM D-4705):	15 lbs.
Breaking Force (ASTM D-2208):	125 lbs.
Elongation (ASTM D-2211):	30-50% at 50 lbs.

#### Flammability

Passes the following flammability tests

California Technical Bulletin 117	Complies
Boston Fire Dept. BFD IX-1	Complies
Cigarette Ignition Resistance (NFPA-260)	Class I (with flame treatment)
Surface Burning Characteristics of Bldg. Materials(ASTM E84)	Class II (Class I with flame treatment)

\*Successfully used in CAL 133 applications with Firegard F187 fire backer material or equivalent.

#### Recommended Cleaning Instructions

Dust regularly. Minor spots can be washed off using lukewarm water and mild soap.

Do not soak. Never clean with abrasive solvents, alcohol, or wax-based products.