

Upholstery Leather      Technical Data

### Leather Specifications

Style:	Prima (PR)
Description:	Full grain, aniline dyed, naked leather
Thickness:	0.9–1.0 mm
Weight:	2.25–2.50 oz. per sq. ft.
Average Hide Size:	55–65 sq. ft.
Finish:	Naked

### Performance Characteristics

### Tests

Light Fastness (AATCC Method 16, Option E, 72 Hours)	Class 2-3
Crocking (ASTM D-5053):	Dry: Class 2-3
Abrasion (ASTM D-3884):	N/A
Flex (ASTM D-2097):	N/A
Tearing Strength, Double Hole (ASTM D-4705):	25 lbs.
Breaking Force (ASTM D-2208):	200 lbs.
Elongation (ASTM D-2211):	30-60% at 50 lbs.

### Flammability

Passes the following flammability tests

California Technical Bulletin 117	Complies
Surface Burning Characteristics of Bldg. Materials (ASTM E84)	Class II

\*Successfully used in CAL 133 applications with Firegard F187 fire backer material or equivalent.

### Recommended Cleaning Instructions

Dust regularly. Minor spots can be washed off using lukewarm water and mild soap.

Do not soak. Never clean with abrasive solvents, alcohol, or wax-based products.

Approved maintenance products are available from Spinneybeck.