

## Salon (SN)

**Upholstery Leather**      Technical Data**Leather Specifications**

Style:	Salon (SN)
Description:	Full grain, aniline dyed, finished leather
Thickness:	1.1–1.2 mm
Weight:	2.75–3.0 oz. per sq. ft.
Average Hide Size:	50–55 sq. ft.
Finish:	Breathable protective finish

**Performance Characteristics****Tests**

Light Fastness (AATCC Method 16, Option E, 72 Hours)	Class 4
Crocking (ASTM D-5053):	Dry: Class 4      Wet: Class 3
Abrasion (ASTM D-3884):	750 cycles (CS-10 wheels)
Flex (ASTM D-2097):	N/A
Tearing Strength, Double Hole (ASTM D-4705):	25 lbs.
Breaking Force (ASTM D-2208):	200 lbs.
Elongation (ASTM D-2211):	30-50% at 50 lbs.

**Flammability***Passes the following flammability tests*

California Technical Bulletin 117	Complies
Surface Burning Characteristics of Bldg. Materials (ASTM E84)	Class II
IMO Resolution A.652 (16)	Complies

\*Successfully used in CAL 133 applications with Firegard F187 fire backer material or equivalent.

**Recommended Cleaning Instructions**

Dust regularly. Minor spots can be washed off using lukewarm water and mild soap.

Do not soak. Never clean with abrasive solvents, alcohol, or wax-based products.

Approved maintenance products are available from Spinneybeck.