

Velluto Pelle (VP)

Upholstery Leather Technical Data

Leather Specifications

Style:	Velluto Pelle (VP)
Description:	Lightly enhanced, aniline dyed, finished leather
Thickness:	1.0–1.1 mm
Weight:	2.50–2.75 oz. per sq. ft.
Average Hide Size:	50–60 sq. ft.
Finish:	Breathable protective finish

Performance Characteristics

Tests

Light Fastness (AATCC Method 16, Option E, 72 Hours)	Class 4
Crocking (ASTM D-5053):	Dry: Class 4-5 Wet: Class 4
Abrasion (ASTM D-3884):	1,000+ cycles (CS-10 wheels)
Flex (ASTM D-2097):	70,000 cycles
Tearing Strength, Double Hole (ASTM D-4705):	25 lbs.
Breaking Force (ASTM D-2208):	150 lbs.
Elongation (ASTM D-2211):	30-50% at 50 lbs.

Flammability

Passes the following flammability tests

California Technical Bulletin 117	Complies
Boston Fire Dept. BFD IX-1	Complies (with flame treatment)
Cigarette Ignition Resistance (NFPA-260)	Class I
Surface Burning Characteristics of Bldg. Materials (ASTM E84)	Class II (Class I with flame treatment)
IMO Resolution A.652 (16)	Complies
IMO Resolution A.653 (16)	Complies

*Successfully used in CAL 133 applications with Firegard F187 fire backer material or equivalent.

Recommended Cleaning Instructions

Dust regularly. Minor spots can be washed off using lukewarm water and mild soap.

Do not soak. Never clean with abrasive solvents, alcohol, or wax-based products.

Approved maintenance products are available from Spinneybeck.