

# Cascia

Upholstery Leather

spinneybeck



**Cascia is a  
naked leather with  
a velvet hand.**


Cascia is named for a town in the mountainous southeastern corner of Umbria. Unique to naked leathers, it has a very consistent color and a supple, velvet hand. The premium select material originates from Scandinavia and its clarity reveals all the natural characteristics of premium full grain leather. A blend of the finest quality aniline dyes provides excellent lightfastness properties for a naked leather.

<b>Product</b>	Cascia (CA)
<b>Content</b>	European cowhide
<b>Origin</b>	Italy
<b>Hide Size</b>	48–50 sq ft (4.5–4.6 sq m)
<b>Thickness</b>	1.3–1.5 mm
<b>Weight</b>	3.25–3.75 oz / sq ft (992–1144 g / sq m)
<b>Grain</b>	Full
<b>Grain Texture</b>	Smooth, tight
<b>Tannage</b>	Chrome
<b>Dye</b>	Aniline
<b>Finish</b>	Naked
<b>Primary Uses</b>	Upholstery, handrails, wall panels, architectural applications
<b>Industry</b>	Contract, hospitality, marine, residential
<b>Maintenance</b>	Wipe entire surface with a soft cloth and cool water to even out any abrasions or stains. Do not spot rub, for it will darken only that area. Occasional use of water-based leather cleaner, conditioner, and protector is recommended. Other leather cleaners such as saddle soap or household cleaners that may contain harsh chemicals, alcohol or ink removers should never be used.
<b>Custom</b>	Custom colors available on a select basis
<b>Special Services</b>	Perforated and embossed available with an upcharge
<b>Variation</b>	Color variation of naked leathers may be more pronounced beyond the normal commercial range. A Cutting for Approval (CFA) is required for all orders.
<b>Colorfastness to Light</b>	Class 2–3
<b>Colorfastness to Crocking</b>	Class 2–3 (dry)
<b>Flammability</b>	CAL 117: Pass CAL 133: Successfully used in CAL 133 applications with Firegard F187 fire backer material or equivalent (flame treated) Cigarette Ignition Resistance NFPA 260: Class 1
<b>Durability + Strength</b>	Abrasion ASTM D 7255: n/a Breaking Force ASTM D 2208: 376 lb Elongation ASTM D 2211: 30–50% at 50 lb Flex ASTM D 2097: n/a Tearing Strength ASTM D 4705: 46 lb


#### Standard Colors



CA 1258



CA 1255



CA 1256



CA 1253



CA 1254




CA 1252



CA 1250



CA 1251



CA 1257



CA BLACK