

Muro

Wall Panel



spinneybeck



Muro elevates with endless possibilities.

Numerous design options combined with Spinneybeck's unparalleled collection of leather styles and colors offer endless possibilities for the wall. Muro panels add character and sophistication to a wide range of wall, headboard, and ceiling applications. Available in almost 1,000 colors, these bespoke leather-wrapped wall panels offer a refined alternative to vertical surfacing. Accent with stitching and fluting, beveled edges, laser engraving, or other embellishment options to enhance and elevate any interior space.




Muro at 777 Partners



Custom Debossed Muro at Greenberg Traurig

Custom Quilted Muro at Sands Capital Management



Embellishment Options

Beveled

Button Tufted

Debossed

Fluted

Laser Engraved

Painted

Quilted

Stitched

Quilted Options

Diamond

Parallel


Rectangle

Square

Product	Muro
Content	European cowhide + Plywood substrate
Minimum Size	1'-0" x 1'-6" (30.5 x 45.7 cm)
Maximum Size	4'-0" x 4'-0" (121.9 x 121.9 cm)
Thickness	1–1 1/8 in (2.5–2.8 cm) (includes Z-Clips)
Substrate Options	Standard or FR (Fire Rated) Plywood
Embellishment Options	Beveled, Button Tufted, Fluted, Laser Engraved, Painted, Quilted, Stitched
Quilted Options	Diamond, Parallel, Rectangle, Square
Custom	FilzFelt© felts and panel sizes beyond the standard minimum and maximum sizes must be quoted
Durability	Contract or residential
Lead Time	Made to order and certain lead times will apply
Maintenance	For finished leathers, wipe with a cool, damp cloth. For tougher soiling, use a pH-balanced soap such as Dawn with a 1:10 ratio of soap to water and rinse. Repeat, if needed. Occasional use of Spinneybeck Finished Leather Cleaner, Conditioner & Protector is recommended. For naked (aniline) leathers, wipe entire surface with a soft cloth and cool water to even out any abrasions or stains. Do not spot rub, for it will darken only that area. Occasional use of Spinneybeck Aniline Leather Cleaner, Conditioner & Protector is recommended. Other leather cleaners such as saddle soap or household cleaners that may contain harsh chemicals, alcohol or ink removers should never be used.
Installation	Install with Z-Clips provided (wall screws not included). The Z-Clips provided are 6 ft (1.8 m) in length and can be cut to fit according to site requirements.
Variation	Color variation of naked leathers may be more pronounced beyond the normal commercial range. A Cutting for Approval (CFA) is required for all orders.

Standard Leathers

Available in the full color range of each leather below—refer to Color Book or spinneybeck.com/colorbook for complete color selection.
(Swatches shown to indicate grain texture only.)



Standard Thread Colors

