


Saddle

Upholstery Leather

spinneybeck

About



Saddle is a full grain, aniline dyed upholstery leather. Inspired by the vegetable tanned leather used for saddlery, Saddle is produced from some of the world's finest and clearest bovine material and is a chromium-tanned leather containing a 100 percent vegetable retannage. The premium, select hides required to produce Saddle originate from Scandinavian countries. The special retannage and ironing combine to produce a fine, tight-grained leather which makes Saddle a favorite of leather aficionados everywhere.



Specifications

Name	Saddle (SL)
Content	European cowhide
Origin	Italy
Hide Size	55–65 ft ² (5.1–6.0 m ²)
Thickness	1.0–1.2 mm
Weight	2.5–3.0 oz / ft ² (763–915 g / m ²)
Grain	Full
Grain Texture	Smooth, tight
Tannage	Combination
Dye	Aniline
Finish	Naked
Primary Uses	Upholstery, handrails, wall panels, architectural applications
Industry	Contract, hospitality, marine, residential
Maintenance	Wipe entire surface with a soft cloth and cool water to even out any abrasions or stains. Do not spot rub, for it will darken only that area. Occasional use of Spinneybeck Aniline Leather Cleaner, Conditioner & Protector or Aniline Leather Maintenance Kit is recommended. Other leather cleaners such as saddle soap or household cleaners that may contain harsh chemicals, alcohol or ink removers should never be used.
Custom	Custom colors not available
Special Services	Perforated and embossed available with an upcharge
Variation	Color variation of naked leathers may be more pronounced beyond the normal commercial range. A Cutting for Approval (CFA) is required for all orders.
Colorfastness to Light	Class 2–3
Colorfastness to Crocking	Class 2–3 (dry)
Flammability	CAL 117: Pass CAL 133: Successfully used in CAL 133 applications with Firegard F187 fire backer material or equivalent
Durability + Strength	Abrasion ASTM D 7255: n/a Breaking Force ASTM D 2208: 200 lb Elongation ASTM D 2211: 30–50% at 50 lb Flex ASTM D 2097: n/a Tearing Strength ASTM D 4705: 25 lb

Standard Colors



SL 0068



SL 0065



SL 0069



SL 0066



SL 0061



SL 0070



SL 0063



SL 0067